Floor screen

Design: Team Glimakra





Floor screen

Design: Team Glimakra



Limbus Light Floor screen is the thinnest member in Limbus by Glimakra. When the acoustics have been taken care of and only effective shielding is required, this fabric-covered screen fits well. It is combined well with other acoustic screens, sofas and ceiling suspended absorbents in Limbus by Glimakra.

DIMENSIONS 600 1000 / 1200 200 1400 / 1600 / 1800 **200** ▶

Other dimensions on request.

Thickness: 20 mm Weight: 16 kg/m²

DESCRIPTION

Body: 19 mm sound reducing light weight MDF.

Upholstery: Upholstered with fabric on both sides. The nails

are covered with a decorative piping.

Angular foot (pair): Powder coated grey 400 x 35 x 8 mm.

Total height leg with foot: about 62 mm.

Installation: The feet are mounted with continuous stud bolt

(M6).

100% recyclable materials.

FABRIC AND PIPING

Look in Product sheet Fabric and piping.pdf for our standard fabrics, you can download it here: http://glimakra.com/en/download/.


Floor screen

Design: Team Glimakra



OPTIONS

Foot: Angular foot, angular foot on lockable castors and single leg. Grey as standard, black and white on request.











Straight

Angle

Three-way

Four-way



Addon: Dimensioned add on screen in acrylic plastic. More information in separate product sheet.



Writingboard: 650 x 970 mm, writing laminate.

CERTIFICATES

Möbelfakta: The product has been declared and approved in accordance with the criteria for floor screens in Möbelfakta ver. 2019-05-01. Reg. 0320151216. Valid until 2025-12-16.



Glimakra of Sweden AB is certified according to ISO 9001:2015 and ISO 14001:2015.





SPECIFICATION TEXT

E.g: Limbus Light Floor screen $1600 \times 1200 \times 20 \text{ mm}$ with two pair angular feet.

Fabric: Blazer CUZ 28 on the inside and Blazer CUZ 30 on the outside. No visible seams. Nails hidden by piping black 190.

Floor screen

Design: Team Glimakra



