

PRODUCT SHEET / 2020 03 04

LimbusConcept Soft

Work booths

Design: Team Glimakra



LimbusConcept Soft


Work booths

Design: Team Glimakra



LimbusConcept Soft workplace in C or H formation targets the need of temporary workplaces for individual focused work at the activity-based office. The flexibility in the system regarding size and the large selection of standard fabrics provide almost unlimited opportunities to customize to most environments. A very important feature is that the sound reducing body significantly reduces the sound propagation in the room. A formation with tabletop increases the sound absorption at low frequencies significantly. LimbusConcept Soft can be fitted with a fixed tabletop.

DIMENSIONS


Basic C:




Basic H:



Extension C:



Extension H:



Other dimensions on request.


Thickness: 33 mm

Fixed tabletop for C and H formation:

Width: 42 mm shorter than the outside dimension of the booth

Other dimensions on request.

Thickness: 33 mm



Depth: 550 / 750 mm

Height tabletop: 750 mm

Height over table: 470 mm

LimbusConcept Soft

Work booths

Design: Team Glimakra



DESCRIPTION

Body: 31 mm acoustic board consisting of sound absorbing polyether (Oeko-Tex) glued on both sides of an 19 mm sound reducing lightweight MDF.

Upholstery: Upholstered with fabric on both sides. The nails are covered with a decorative piping.

Feet: Adjustable feet mounted directly on the screen.

Cable feedthrough: Ø80 mm, between workplaces.

Fixed tabletop: Veneer or laminate with cable feedthrough in aluminium. Located in the middle.

Mounting: The screens are connected underneath the tabletop with two visible brackets in each corner fastened with wooden screws directly into the screen. The tabletop is fitted with custom-made wooden rails. Delivered unassembled.

100% recyclable materials.

FABRIC AND PIPING

Look in Product sheet Fabric and piping.pdf for our standard fabrics, you can download it here: <http://glimakra.com/en/download/>.


OPTIONS

Tabletop: Veneer 22 mm in ash, birch, beech or oak; laminate 22 mm in birch, beech, oak, white, black or grey.


Power, data, USB: The worktop can be equipped with Powerdot or Axessline outlets.

External toolbar: Aluminium and white. A variety of accessories are available. See price list under LimbusDeskup Toolbar / Accessory for current accessories.

Legs: Powder coated grey 20x20 mm. Total height leg approx. 65 mm.



Addon: Dimensioned add on screen in acrylic plastic. More information in separate product sheet.



TableLamp: With integrated table fitting. More information in separate product sheet.

CERTIFICATES

Acoustics: Measurements made in accordance with ISO 354:2003. Evaluation made according to standards for individual objects SS 25269:2013 (Report 13-187-M3, Date 2013-12-17, Akustikverkstan, laboratory accredited by Swedac)

Möbelfakta: The product meets the requirements for environment and social responsibility defined by Möbelfakta.

Glimakra of Sweden AB is certified according to ISO 9001:2015 and ISO 14001:2015.



SPECIFICATION TEXT


E.g: Glimakra LimbusConcept Soft H formation
1686 x 1640 x 1220 mm.

Sound absorbing filling on both sides of an 19 mm sound reducing lightweight MDF.

Fabric: Blazer CUZ 28 on the inside and Blazer CUZ 30 on the outside. No visible seams. Nails hidden by piping black 190.

Acoustics evaluated according to SS 25269.

2 fixed tabletops in veneer 22 mm ash.



Equivalent absorption area per m² screen surface (m²S/m²)

The values are to be multiplied by the screen area.

PRODUCT SHEET / 2020 03 04

LimbusConcept Soft

Work booths

Design: Team Glimakra

